



DET NORSKE VERITAS

TYPE APPROVAL CERTIFICATE

CERTIFICATE NO. **E-12948**

This is to certify that the
Low Voltage Cable

with type designation(s)
DP 250V Non-Armoured, Flame retardant, Halogen free, Low smoke Control & Instrumentation cables

Issued to
TELDOR Cables & Systems Ltd.
Israel, Israel

is found to comply with
Det Norske Veritas' Rules for Classification of Ships, High Speed & Light Craft and Det Norske Veritas' Offshore Standards

IEC 60092-376 (2003-05)
IEC 60332-3-22 (2009-02)
IEC 60332-3-24 (2009-02)
IEC 60754-1/2 (2011-11)
IEC61034-1/2 (2005-04/2005-04)

Application
Control and instrumentation. Non-armoured.
Flame retardant in bunch Cat. A or Cat. C. Halogen free. Low smoke.
Mud resistant (Optional)

Voltage class (V) 150/250V
Temp. class (°C) 90

This Certificate is valid until **2017-12-31**.

Issued at **Høvik** on **2014-03-28**

DNV local station: **Piraeus**

Approval Engineer: **Ivar Bull**

for **Det Norske Veritas AS**

.....
Marit Laumann
Head of Section

This Certificate is subject to terms and conditions overleaf. Any significant change in design or construction may render this Certificate invalid.

The validity date relates to the Type Approval Certificate and not to the approval of equipment/systems installed.

If any person suffers loss or damage which is proved to have been caused by any negligent act or omission of Det Norske Veritas, then Det Norske Veritas shall pay compensation to such person for his proved direct loss or damage. However, the compensation shall not exceed an amount equal to ten times the fee charged for the service in question, provided that the maximum compensation shall never exceed USD 2 million. In this provision "Det Norske Veritas" shall mean the Foundation Det Norske Veritas as well as all its subsidiaries, directors, officers, employees, agents and any other acting on behalf of Det Norske Veritas.

Product description

Type: DF 250 V with braid

Construction:

Conductors: Tinned, stranded copper class 2 or class 5
Core insulation: HF XLPE
Screen: Copper or aluminum backed polyester tape w/tinned copper drain wire
Inner sheath: SHF2
Metal covering: Metal wire braid made of bare or tinned copper, galvanized steel, aluminum alloy, copper alloy or bronze
Sheath: SHF2 or SHF MUD, single or double layer

SINGLE CORES:

Number of cores x conductor cross-section	Overall diameter
mm ²	Nominal mm
2 x 0,5	8,2
3 x 0,5	8,5
4 x 0,5	8,9
5 x 0,5	9,3
6 x 0,5	9,8
7 x 0,5	9,8
8 x 0,5	10,5
9 x 0,5	11,1
10 x 0,5	11,6
11 x 0,5	11,6
12 x 0,5	12,1
13 x 0,5	12,5
14 x 0,5	12,5
15 x 0,5	12,9
16 x 0,5	12,9
17 x 0,5	13,9
18 x 0,5	13,9
19 x 0,5	13,9
20 x 0,5	14,4
21 x 0,5	14,4
22 x 0,5	15,2
23 x 0,5	15,2
24 x 0,5	15,7
25 x 0,5	15,7
26 x 0,5	15,7
27 x 0,5	15,9
28 x 0,5	16,6
29 x 0,5	16,6
30 x 0,5	16,6
31 x 0,5	17,0
32 x 0,5	17,0
33 x 0,5	17,0
34 x 0,5	17,5
35 x 0,5	17,5
36 x 0,5	17,5
37 x 0,5	17,5
38 x 0,5	18,2
39 x 0,5	18,2
40 x 0,5	18,2
2 x 0,75	9,0

Number of cores x conductor cross-section	Overall diameter
mm ²	Nominal mm
3 x 0,75	9,3
4 x 0,75	9,8
5 x 0,75	10,4
6 x 0,75	11,0
7 x 0,75	11,0
8 x 0,75	12,3
9 x 0,75	13,0
10 x 0,75	13,9
11 x 0,75	13,9
12 x 0,75	14,2
13 x 0,75	14,9
14 x 0,75	14,9
15 x 0,75	15,5
16 x 0,75	15,5
17 x 0,75	16,3
18 x 0,75	16,3
19 x 0,75	16,3
20 x 0,75	17,0
21 x 0,75	17,0
22 x 0,75	17,8
23 x 0,75	17,8
24 x 0,75	18,5
25 x 0,75	18,5
26 x 0,75	18,5
27 x 0,75	18,8
28 x 0,75	19,3
29 x 0,75	19,3
30 x 0,75	19,3
31 x 0,75	19,9
32 x 0,75	19,9
33 x 0,75	19,9
34 x 0,75	20,9
35 x 0,75	20,9
36 x 0,75	20,9
37 x 0,75	20,9
38 x 0,75	21,6
39 x 0,75	21,6
40 x 0,75	21,6
2 x 1	9,2
3 x 1	9,5

Number of cores x conductor cross-section	Overall diameter
mm ²	Nominal mm
4 x 1	10,1
5 x 1	10,7
6 x 1	11,5
7 x 1	11,5
8 x 1	12,6
9 x 1	13,9
10 x 1	14,3
11 x 1	14,3
12 x 1	14,6
13 x 1	15,4
14 x 1	15,4
15 x 1	16,2
16 x 1	16,2
17 x 1	16,8
18 x 1	16,8
19 x 1	16,8
20 x 1	17,5
21 x 1	17,5
22 x 1	18,4
23 x 1	18,4
24 x 1	19,1
25 x 1	19,1
26 x 1	19,1
27 x 1	19,4
28 x 1	20,0
29 x 1	20,0
30 x 1	20,0
31 x 1	21,0
32 x 1	21,0
33 x 1	21,0
34 x 1	21,6
35 x 1	21,6
36 x 1	21,6
37 x 1	21,6
38 x 1	22,3
39 x 1	22,3
40 x 1	22,3
2 x 1,5	10,2
3 x 1,5	10,6
4 x 1,5	11,5

Number of cores x conductor cross-section	Overall diameter
mm ²	Nominal mm
5 x 1,5	12,4
6 x 1,5	13,7
7 x 1,5	13,7
8 x 1,5	15,1
9 x 1,5	16,2
10 x 1,5	16,7
11 x 1,5	16,7
12 x 1,5	17,1
13 x 1,5	18,0
14 x 1,5	18,0
15 x 1,5	18,7
16 x 1,5	18,7
17 x 1,5	19,5
18 x 1,5	19,5
19 x 1,5	19,5
20 x 1,5	20,8
21 x 1,5	20,8
22 x 1,5	21,6
23 x 1,5	21,6
24 x 1,5	22,5
25 x 1,5	22,5
26 x 1,5	22,5
27 x 1,5	22,9
28 x 1,5	23,8
29 x 1,5	23,8

Number of cores x conductor cross-section	Overall diameter
mm ²	Nominal mm
30 x 1,5	23,8
31 x 1,5	24,7
32 x 1,5	24,7
33 x 1,5	24,7
34 x 1,5	25,5
35 x 1,5	25,5
36 x 1,5	25,5
37 x 1,5	25,5
38 x 1,5	26,6
39 x 1,5	26,6
40 x 1,5	26,6
2 x 2,5	11,0
3 x 2,5	11,7
4 x 2,5	12,7
5 x 2,5	14,0
6 x 2,5	15,1
7 x 2,5	15,1
8 x 2,5	16,7
9 x 2,5	17,9
10 x 2,5	18,5
11 x 2,5	18,5
12 x 2,5	19,0
13 x 2,5	19,7
14 x 2,5	19,7
15 x 2,5	21,0

Number of cores x conductor cross-section	Overall diameter
mm ²	Nominal mm
16 x 2,5	21,0
17 x 2,5	21,9
18 x 2,5	21,9
19 x 2,5	21,9
20 x 2,5	22,9
21 x 2,5	22,9
22 x 2,5	24,1
23 x 2,5	24,1
24 x 2,5	25,3
25 x 2,5	25,3
26 x 2,5	25,3
27 x 2,5	25,8
28 x 2,5	26,7
29 x 2,5	26,7
30 x 2,5	26,7
31 x 2,5	27,6
32 x 2,5	27,6
33 x 2,5	27,6
34 x 2,5	28,5
35 x 2,5	28,5
36 x 2,5	28,5
37 x 2,5	28,5
38 x 2,5	29,9
39 x 2,5	29,9
40 x 2,5	29,9

PAIRS:

Number of pairs x conductor cross-section	Overall diameter
mm ²	Nominal mm
2 x2 x 0,5	10,7
3 x2 x 0,5	11,2
4 x2 x 0,5	12,3
5 x2 x 0,5	13,6
6 x2 x 0,5	14,4
7 x2 x 0,5	14,4
8 x2 x 0,5	15,9
9 x2 x 0,5	17,1
10 x2 x 0,5	17,9
11 x2 x 0,5	17,9
12 x2 x 0,5	18,3
13 x2 x 0,5	19,1
14 x2 x 0,5	19,1
15 x2 x 0,5	19,9
16 x2 x 0,5	19,9
17 x2 x 0,5	21,1
18 x2 x 0,5	21,1
19 x2 x 0,5	21,1
20 x2 x 0,5	22,1
21 x2 x 0,5	22,1
22 x2 x 0,5	23,0

Number of pairs x conductor cross-section	Overall diameter
mm ²	Nominal mm
23 x2 x 0,5	23,0
24 x2 x 0,5	24,2
25 x2 x 0,5	24,2
26 x2 x 0,5	24,2
27 x2 x 0,5	24,8
28 x2 x 0,5	25,6
29 x2 x 0,5	25,6
30 x2 x 0,5	25,6
31 x2 x 0,5	26,6
32 x2 x 0,5	26,6
33 x2 x 0,5	26,6
34 x2 x 0,5	27,4
35 x2 x 0,5	27,4
36 x2 x 0,5	27,4
37 x2 x 0,5	27,4
38 x2 x 0,5	28,4
39 x2 x 0,5	28,4
40 x2 x 0,5	28,4
41 x2 x 0,5	29,7
42 x2 x 0,5	29,7
43 x2 x 0,5	29,7

Number of pairs x conductor cross-section	Overall diameter
mm ²	Nominal mm
44 x2 x 0,5	30,7
45 x2 x 0,5	30,7
46 x2 x 0,5	30,7
47 x2 x 0,5	30,7
48 x2 x 0,5	31,1
49 x2 x 0,5	32,1
50 x2 x 0,5	32,1
2 x2 x 0,75	12,3
3 x2 x 0,75	12,9
4 x2 x 0,75	14,3
5 x2 x 0,75	15,5
6 x2 x 0,75	16,7
7 x2 x 0,75	16,7
8 x2 x 0,75	18,5
9 x2 x 0,75	19,7
10 x2 x 0,75	20,8
11 x2 x 0,75	20,8
12 x2 x 0,75	21,3
13 x2 x 0,75	22,2
14 x2 x 0,75	22,2
15 x2 x 0,75	23,4

Number of pairs x conductor cross-section	Overall diameter
mm ²	Nominal mm
16 x2 x 0,75	23,4
17 x2 x 0,75	24,7
18 x2 x 0,75	24,7
19 x2 x 0,75	24,7
20 x2 x 0,75	25,8
21 x2 x 0,75	25,8
22 x2 x 0,75	27,2
23 x2 x 0,75	27,2
24 x2 x 0,75	28,3
25 x2 x 0,75	28,3
26 x2 x 0,75	28,3
27 x2 x 0,75	29,2
28 x2 x 0,75	30,1
29 x2 x 0,75	30,1
30 x2 x 0,75	30,1
31 x2 x 0,75	31,2
32 x2 x 0,75	31,2
33 x2 x 0,75	31,2
34 x2 x 0,75	32,4
35 x2 x 0,75	32,4
36 x2 x 0,75	32,4
37 x2 x 0,75	32,4
38 x2 x 0,75	33,7
39 x2 x 0,75	33,7
40 x2 x 0,75	33,7
41 x2 x 0,75	35,6
42 x2 x 0,75	35,6
43 x2 x 0,75	35,6
44 x2 x 0,75	36,8
45 x2 x 0,75	36,8
46 x2 x 0,75	36,8
47 x2 x 0,75	36,8
48 x2 x 0,75	37,5
49 x2 x 0,75	38,6
50 x2 x 0,75	38,6
2 x2 x 1	12,9
3 x2 x 1	14,0
4 x2 x 1	15,1
5 x2 x 1	16,4
6 x2 x 1	17,5
7 x2 x 1	17,5
8 x2 x 1	19,4
9 x2 x 1	21,1
10 x2 x 1	21,9
11 x2 x 1	21,9
12 x2 x 1	22,5
13 x2 x 1	23,6
14 x2 x 1	23,6
15 x2 x 1	24,9
16 x2 x 1	24,9
17 x2 x 1	26,0
18 x2 x 1	26,0
19 x2 x 1	26,0

Number of pairs x conductor cross-section	Overall diameter
mm ²	Nominal mm
20 x2 x 1	27,4
21 x2 x 1	27,4
22 x2 x 1	28,9
23 x2 x 1	28,9
24 x2 x 1	30,3
25 x2 x 1	30,3
26 x2 x 1	30,3
27 x2 x 1	30,9
28 x2 x 1	32,1
29 x2 x 1	32,1
30 x2 x 1	32,1
31 x2 x 1	33,3
32 x2 x 1	33,3
33 x2 x 1	33,3
34 x2 x 1	35,0
35 x2 x 1	35,0
36 x2 x 1	35,0
37 x2 x 1	35,0
38 x2 x 1	36,4
39 x2 x 1	36,4
40 x2 x 1	36,4
41 x2 x 1	37,9
42 x2 x 1	37,9
43 x2 x 1	37,9
44 x2 x 1	39,3
45 x2 x 1	39,3
46 x2 x 1	39,3
47 x2 x 1	39,3
48 x2 x 1	39,9
49 x2 x 1	41,0
50 x2 x 1	41,0
2 x2 x 1,5	15,4
3 x2 x 1,5	16,3
4 x2 x 1,5	17,5
5 x2 x 1,5	19,0
6 x2 x 1,5	20,8
7 x2 x 1,5	20,8
8 x2 x 1,5	22,9
9 x2 x 1,5	24,9
10 x2 x 1,5	25,8
11 x2 x 1,5	25,8
12 x2 x 1,5	26,8
13 x2 x 1,5	27,9
14 x2 x 1,5	27,9
15 x2 x 1,5	29,7
16 x2 x 1,5	29,7
17 x2 x 1,5	31,0
18 x2 x 1,5	31,0
19 x2 x 1,5	31,0
20 x2 x 1,5	33,0
21 x2 x 1,5	33,0
22 x2 x 1,5	35,0
23 x2 x 1,5	35,0

Number of pairs x conductor cross-section	Overall diameter
mm ²	Nominal mm
24 x2 x 1,5	36,8
25 x2 x 1,5	36,8
26 x2 x 1,5	36,8
27 x2 x 1,5	37,7
28 x2 x 1,5	39,1
29 x2 x 1,5	39,1
30 x2 x 1,5	39,1
31 x2 x 1,5	40,4
32 x2 x 1,5	40,4
33 x2 x 1,5	40,4
34 x2 x 1,5	42,2
35 x2 x 1,5	42,2
36 x2 x 1,5	42,2
37 x2 x 1,5	42,2
38 x2 x 1,5	43,9
39 x2 x 1,5	43,9
40 x2 x 1,5	43,9
41 x2 x 1,5	45,7
42 x2 x 1,5	45,7
43 x2 x 1,5	45,7
44 x2 x 1,5	47,4
45 x2 x 1,5	47,4
46 x2 x 1,5	47,4
47 x2 x 1,5	47,4
48 x2 x 1,5	48,1
49 x2 x 1,5	49,5
50 x2 x 1,5	49,5
2 x2 x 2,5	17,0
3 x2 x 2,5	18,0
4 x2 x 2,5	19,4
5 x2 x 2,5	21,3
6 x2 x 2,5	22,9
7 x2 x 2,5	22,9
8 x2 x 2,5	25,7
9 x2 x 2,5	27,8
10 x2 x 2,5	29,3
11 x2 x 2,5	29,3
12 x2 x 2,5	30,1
13 x2 x 2,5	31,4
14 x2 x 2,5	31,4
15 x2 x 2,5	33,4
16 x2 x 2,5	33,4
17 x2 x 2,5	35,7
18 x2 x 2,5	35,7
19 x2 x 2,5	35,7
20 x2 x 2,5	37,7
21 x2 x 2,5	37,7
22 x2 x 2,5	39,7
23 x2 x 2,5	39,7
24 x2 x 2,5	41,8
25 x2 x 2,5	41,8
26 x2 x 2,5	41,8
27 x2 x 2,5	42,6

Number of pairs x conductor cross-section	Overall diameter
mm ²	Nominal mm
28 x2 x 2,5	44,2
29 x2 x 2,5	44,2
30 x2 x 2,5	44,2
31 x2 x 2,5	46,0
32 x2 x 2,5	46,0
33 x2 x 2,5	46,0
34 x2 x 2,5	47,8
35 x2 x 2,5	47,8

Number of pairs x conductor cross-section	Overall diameter
mm ²	Nominal mm
36 x2 x 2,5	47,8
37 x2 x 2,5	47,8
38 x2 x 2,5	49,9
39 x2 x 2,5	49,9
40 x2 x 2,5	49,9
41 x2 x 2,5	51,8
42 x2 x 2,5	51,8
43 x2 x 2,5	51,8

Number of pairs x conductor cross-section	Overall diameter
mm ²	Nominal mm
44 x2 x 2,5	53,7
45 x2 x 2,5	53,7
46 x2 x 2,5	53,7
47 x2 x 2,5	53,7
48 x2 x 2,5	54,7
49 x2 x 2,5	56,3
50 x2 x 2,5	56,3

TRIPLES:

Number of triples x conductor cross-section	Overall diameter
mm ²	Nominal mm
1x3 x0,5	8,5
2x3 x0,5	11,7
3x3 x0,5	12,4
4x3 x0,5	13,8
5x3 x0,5	14,9
6x3 x0,5	15,8
7x3 x0,5	15,8
8x3 x0,5	17,5
9x3 x0,5	18,8
10x3 x0,5	19,5
11x3 x0,5	19,5
12x3 x0,5	20,0
13x3 x0,5	21,2
14x3 x0,5	21,2
15x3 x0,5	22,2
16x3 x0,5	22,2
17x3 x0,5	23,1
18x3 x0,5	23,1
19x3 x0,5	23,1
20x3 x0,5	24,6
21x3 x0,5	24,6
22x3 x0,5	25,7
23x3 x0,5	25,7
24x3 x0,5	27,0
25x3 x0,5	27,0
26x3 x0,5	27,0
27x3 x0,5	27,5
28x3 x0,5	28,3
29x3 x0,5	28,3
30x3 x0,5	28,3
31x3 x0,5	29,7
32x3 x0,5	29,7
33x3 x0,5	29,7
34x3 x0,5	30,6
35x3 x0,5	30,6
36x3 x0,5	30,6
1x3 x0,75	9,2

Number of triples x conductor cross-section	Overall diameter
mm ²	Nominal mm
2x3 x0,75	13,8
3x3 x0,75	14,5
4x3 x0,75	15,7
5x3 x0,75	17,0
6x3 x0,75	18,4
7x3 x0,75	18,4
8x3 x0,75	20,4
9x3 x0,75	21,9
10x3 x0,75	22,7
11x3 x0,75	22,7
12x3 x0,75	23,6
13x3 x0,75	24,8
14x3 x0,75	24,8
15x3 x0,75	25,9
16x3 x0,75	25,9
17x3 x0,75	27,3
18x3 x0,75	27,3
19x3 x0,75	27,3
20x3 x0,75	28,8
21x3 x0,75	28,8
22x3 x0,75	30,3
23x3 x0,75	30,3
24x3 x0,75	31,9
25x3 x0,75	31,9
26x3 x0,75	31,9
27x3 x0,75	32,4
28x3 x0,75	33,7
29x3 x0,75	33,7
30x3 x0,75	33,7
31x3 x0,75	35,5
32x3 x0,75	35,5
33x3 x0,75	35,5
34x3 x0,75	36,7
35x3 x0,75	36,7
36x3 x0,75	36,7
1x3 x1	9,5
2x3 x1	14,4

Number of triples x conductor cross-section	Overall diameter
mm ²	Nominal mm
3x3 x1	15,3
4x3 x1	16,6
5x3 x1	18,0
6x3 x1	19,3
7x3 x1	19,3
8x3 x1	21,6
9x3 x1	23,1
10x3 x1	24,2
11x3 x1	24,2
12x3 x1	25,0
13x3 x1	26,3
14x3 x1	26,3
15x3 x1	27,5
16x3 x1	27,5
17x3 x1	29,2
18x3 x1	29,2
19x3 x1	29,2
20x3 x1	30,6
21x3 x1	30,6
22x3 x1	32,3
23x3 x1	32,3
24x3 x1	33,9
25x3 x1	33,9
26x3 x1	33,9
27x3 x1	35,0
28x3 x1	36,3
29x3 x1	36,3
30x3 x1	36,3
31x3 x1	37,8
32x3 x1	37,8
33x3 x1	37,8
34x3 x1	39,2
35x3 x1	39,2
36x3 x1	39,2
1x3 x1,5	10,6
2x3 x1,5	16,9
3x3 x1,5	17,9

Number of triples x conductor cross-section	Overall diameter
mm ²	Nominal mm
4x3 x1,5	19,3
5x3 x1,5	21,2
6x3 x1,5	22,7
7x3 x1,5	22,7
8x3 x1,5	25,5
9x3 x1,5	27,6
10x3 x1,5	28,8
11x3 x1,5	28,8
12x3 x1,5	29,9
13x3 x1,5	31,2
14x3 x1,5	31,2
15x3 x1,5	33,1
16x3 x1,5	33,1
17x3 x1,5	35,4
18x3 x1,5	35,4
19x3 x1,5	35,4
20x3 x1,5	37,3
21x3 x1,5	37,3
22x3 x1,5	39,3
23x3 x1,5	39,3
24x3 x1,5	41,5
25x3 x1,5	41,5
26x3 x1,5	41,5

Number of triples x conductor cross-section	Overall diameter
mm ²	Nominal mm
27x3 x1,5	42,3
28x3 x1,5	43,8
29x3 x1,5	43,8
30x3 x1,5	43,8
31x3 x1,5	45,6
32x3 x1,5	45,6
33x3 x1,5	45,6
34x3 x1,5	47,4
35x3 x1,5	47,4
36x3 x1,5	47,4
1x3 x2,5	11,7
2x3 x2,5	18,7
3x3 x2,5	19,7
4x3 x2,5	21,6
5x3 x2,5	23,5
6x3 x2,5	25,6
7x3 x2,5	25,6
8x3 x2,5	28,5
9x3 x2,5	31,0
10x3 x2,5	32,5
11x3 x2,5	32,5
12x3 x2,5	33,6
13x3 x2,5	35,9

Number of triples x conductor cross-section	Overall diameter
mm ²	Nominal mm
14x3 x2,5	35,9
15x3 x2,5	37,8
16x3 x2,5	37,8
17x3 x2,5	39,9
18x3 x2,5	39,9
19x3 x2,5	39,9
20x3 x2,5	42,3
21x3 x2,5	42,3
22x3 x2,5	44,5
23x3 x2,5	44,5
24x3 x2,5	46,9
25x3 x2,5	46,9
26x3 x2,5	46,9
27x3 x2,5	47,9
28x3 x2,5	49,8
29x3 x2,5	49,8
30x3 x2,5	49,8
31x3 x2,5	51,6
32x3 x2,5	51,6
33x3 x2,5	51,6
34x3 x2,5	53,6
35x3 x2,5	53,6
36x3 x2,5	53,6

Application/Limitation

The requirements of SOLAS Amendments Chapter II-1, Part D, Reg. 45, 5.2 (provision to be taken to limit Fire Propagation along Bundles of Cables or Wires) are fulfilled without any additional measures.

Type Approval documentation

Data sheet: DP type

Test reports: Certificate of Test per DNV Instrumentation and Control cables IEC 60092-376 P/N DG-01P05T12T01 dated December 5, 2013

Tests carried out

Standard	Issued	General description	Limitation
IEC 60092-350	2008-02	General construction and test methods of power, control and instrumentation cables for shipboard and offshore applications	
IEC 60092-351	2004-04	Insulating materials for shipboard and offshore units, power, control, instrumentation, telecommunication and data cables	
IEC 60092-359	1999-08	Sheathing materials for shipboard power and telecommunication cables	
IEC 60092-376	2003-05	Cables for control and instrumentation circuits 150/250 V (300 V)	
IEC 60332-3-22	2009-02	Tests on electric and optical fibre cables under fire conditions – Part 3-22: Test for vertical flame spread of vertically-mounted bunched wires or cables – Category A	Bunch test Category A
IEC 60332-3-24	2009-02	Tests on electric and optical fibre cables under fire conditions – Part 3-24: Test for vertical flame spread of vertically-mounted bunched wires or cables – Category C	Bunch test

Standard	Issued	General description	Limitation
IEC 60754-1	2011-11	Test on gases evolved during combustion of materials from cables – Determination of the amount of halogen acid gas	Low Halogen: <0,5% Halogen
IEC 60754-2	2011-11	Test on gases evolved during combustion of materials from cables – Determination of the degree of acidity of gases evolved during the combustion of materials taken from electric cables by measuring pH and conductivity	Halogen free: pH > 4,3 Conductivity < 10µS
IEC 61034-1/2	2005-04	Measurement of smoke density of cables burning under defined conditions – Test apparatus, procedure and requirements	Low smoke

Marking of product

Teldor – DF type – Size – 150/250V – IEC 60332-3-22 Cat.A or Cat C – Lot No.

Certificate retention survey

The scope of the retention/renewal survey is to verify that the conditions stipulated for the Type approval is complied with and that no alterations are made to the product design or choice of materials.

The main elements of the survey are:

- Inspection on factory samples, selected at random from the production line (where practicable)
- Results from Production Sample Tests (PST) and Routine Tests (RT) checked
- (if RT- and PST-test reports are not available, tests according to PST and RT to be carried out)
- Review of type approval documentation
- Review of possible change in design, materials and performance
- Ensure traceability between manufacturer's product type marking and Type Approval Certificate.

Survey shall be performed at least every second year.

END OF CERTIFICATE