


## Cat. 7 2x(4x2x23/1 AWG) S/FTP FR-LSZH

**Part Number:** 9928002129



**Applications:** Data processing and information systems, Fixed or portable installations, High data rates, Indoor use, fixed installations

**General Construction:** Two groups of 4 individually foil-shielded twisted pairs, cabled together with tinned copper drain conductor, overall braid-shielded and jacketed.  
The cable conforms to IEC 61156-5 Cat. 7, Cat. 6<sub>A</sub> Cat. 6, and Cat. 5e requirements and tested up to 1000 MHz. The two groups are laid in parallel in a FIG-8 ("Siamese") formation.

**Detailed Schematic:**

**Outer Jacket Material:** FR-LSZH

**Weight:** 100 kg/km

### Design & Materials

|   |                              |
|---|------------------------------|
| <b>Conductor Material:</b>              | Annealed Bare Copper         |
| <b>Conductor Size:</b>                  | 23 AWG                       |
| <b>Conductor Construction:</b>          | Solid                        |
| <b>Insulation Material:</b>             | Cellular PO                  |
| <b>Insulation O.D.:</b>                 | 1.38 mm nom.                 |
| <b>Conductor unit identification:</b>   | Solid/stripe                 |
| <b>Color Code:</b>                      | Per TIA/EIA 568-B            |
| <b>Ind. Shield Material:</b>            | Aluminum/Polyester Foil      |
| <b>Ind. Shield Design:</b>              | 100% Coverage                |
| <b>Conductor unit lay-up:</b>           | Pairs                        |
| <b>Overall Braid Shield:</b>            | Yes                          |
| <b>Braid Coverage:</b>                  | 35 % nom.                    |
| <b>Overall Drain-wire Material:</b>     | Annealed Tinned Copper       |
| <b>Overall Drain-wire size:</b>         | 0.41 mm                      |
| <b>Overall Drain-wire Construction:</b> | Solid                        |
| <b>Total number of conductors:</b>      | 8                            |
| <b>Outer Jacket Dimension - X:</b>      | 7.1 mm nom.                  |
| <b>Outer Jacket Dimension - Y:</b>      | 14.7 mm nom.                 |
| <b>Outer Jacket Color:</b>              | Light Gray                   |
| <b>Marking:</b>                         | Per request, Teldor Standard |

### Standards

|                              |  |
|------------------------------|--|
| <b>Applicable Standards:</b> | IEC 61156, ISO/IEC 11801-1, RoHS 3 2015/863/EU |
| <b>Flammability Rating:</b>  | IEC 60332-1, UL 1581 VW-1                      |

## Electrical Properties:

### Cat. 7 Horizontal Cables\*

| Freq. MHz | Attenuation dB/100m 20°C |        | PS NEXT Loss dB |        | NEXT Loss dB  |        | RL dB         |        | PS ANEXT dB   |        | PS ELFEXT dB  |        | ELFEXT dB     |        |
|-----------|--------------------------|--------|-----------------|--------|---------------|--------|---------------|--------|---------------|--------|---------------|--------|---------------|--------|
|           | Typical Value            | Cat. 7 | Typical Value   | Cat. 7 | Typical Value | Cat. 7 | Typical Value | Cat. 7 | Typical Value | Cat. 7 | Typical Value | Cat. 7 | Typical Value | Cat. 7 |
| 1         | 2.0                      | 2.0    | 105.0           | 75.0   | 108.0         | 78.0   | 22.0          | 20.0   | 68.0          | N/A    | 95.0          | 75.0   | 98.0          | 78.0   |
| 4         | 3.6                      | 3.7    | 98.0            | 75.0   | 101.0         | 78.0   | 25.0          | 23.0   | 68.0          | N/A    | 90.0          | 75.0   | 93.0          | 78.0   |
| 10        | 5.6                      | 5.8    | 95.0            | 75.0   | 98.0          | 78.0   | 28.0          | 25.0   | 68.0          | N/A    | 86.0          | 71.0   | 89.0          | 74.0   |
| 20        | 7.9                      | 8.3    | 90.0            | 75.0   | 93.0          | 78.0   | 28.0          | 25.0   | 68.0          | N/A    | 80.0          | 65.0   | 83.0          | 68.0   |
| 30        | 9.7                      | 10.2   | 85.0            | 75.0   | 88.0          | 78.0   | 27.0          | 23.8   | 68.0          | N/A    | 76.0          | 61.5   | 79.0          | 64.5   |
| 100       | 18.0                     | 19.0   | 80.0            | 69.4   | 83.0          | 72.4   | 24.0          | 21.1   | 68.0          | N/A    | 66.0          | 51.0   | 69.0          | 54.0   |
| 150       | 22.4                     | 23.6   | 78.0            | 66.7   | 81.0          | 69.7   | 22.0          | 18.8   | 65.0          | N/A    | 63.0          | 47.5   | 66.0          | 50.5   |
| 200       | 26.0                     | 27.5   | 78.0            | 65.0   | 81.0          | 68.0   | 21.0          | 18.0   | 65.0          | N/A    | 60.0          | 45.0   | 63.0          | 48.0   |
| 250       | 29.4                     | 31.0   | 75.0            | 63.4   | 78.0          | 66.4   | 20.0          | 17.3   | 62.0          | N/A    | 58.0          | 43.0   | 61.0          | 46.0   |
| 300       | 32.5                     | 34.2   | 75.0            | 62.2   | 78.0          | 65.2   | 19.0          | 17.3   | 62.0          | N/A    | 52.0          | 41.5   | 55.0          | 44.5   |
| 400       | 38.0                     | 40.0   | 70.0            | 60.4   | 73.0          | 63.4   | 19.0          | 17.3   | 62.0          | N/A    | 49.0          | 38.9   | 52.0          | 41.9   |
| 500       | 43.0                     | 45.2   | 70.0            | 58.9   | 73.0          | 61.9   | 19.0          | 17.3   | 62.0          | N/A    | 47.0          | 37.0   | 50.0          | 40.0   |
| 600       | 47.6                     | 50.1   | 70.0            | 57.7   | 73.0          | 60.7   | 19.0          | 17.3   | 62.0          | N/A    | 45.0          | 35.4   | 48.0          | 38.4   |

\*Supplied cables meet the minimum Cat. 7 transmission requirements as per **IEC 61156-5 Ed. 2**

## Performance

|                                       |                 |
|---------------------------------------|-----------------|
| <b>Frequency Range:</b>               | 1 - 600 MHz     |
| <b>Impedance:</b>                     | 100 Ω           |
| <b>Coupling Attenuation:</b>          | Type I          |
| <b>Max. DC Resistance :</b>           | 73 Ω/km@20°C    |
| <b>Max. Resistance Unbalance:</b>     | 2 %             |
| <b>Capacitance Unbalance:</b>         | 1.2 pF/m max.   |
| <b>Velocity of Propagation:</b>       | 78 % nom.       |
| <b>Propagation Delay Skew:</b>        | 25 ns/100m max. |
| <b>Dielectric Strength:</b>           | 700 V/minute    |
| <b>Dielectric Strength to Shield:</b> | 700 V/minute    |
| <b>Min. Insulation Resistance :</b>   | 5 GΩ•km         |
| <b>Min. Bend Radius:</b>              | 60 mm           |
| <b>Max. Operating Temperature:</b>    | +65 °C          |
| <b>Min. Operating Temperature:</b>    | -40 °C          |

| Prepared By  | Revised By    | Version Num | Modified on |
|--------------|---------------|-------------|-------------|
| Asher Bohbut | Jacob Ben Ary | 2.6         | 12-06-2013  |

Teldor Cables & Systems Ltd. ("Teldor") reserves the right to make changes to the products described in this catalog without prior notice. Teldor does not assume any liability which may occur due to the use of the products described herein. Drawings may not be to scale and are provided for general and informational purposes only. The information contained in this catalog is the proprietary property of Teldor, and may not be used, reproduced or disclosed to others, in whole or in part, without the written authorization of Teldor.

**Teldor Cables & Systems Ltd.** - Ein-Dor, 1933500  
6770650

ISRAEL

Tel: +972 4 6770555

Fax: +972 4