

Cat.7 1000 MHz 2x4x2x23/1AWG FIG-8 S/FTP FR-LSZH

Part Number: 99280S2129

Applications: Data-Centers/SANs, High data rates, Indoor use, fixed installations, High bandwidth digital applications with low BER


General Construction: The cable contains two groups of 4 individually foil-shielded twisted pairs (aluminum face upward), cabled together with a drain wire, and overall braid-shielded. The two groups are laid in parallel in a Fig-8 ("Siamese") formation and jacketed.

Detailed Schematic:

Outer Jacket Material: FR-LSZH

Outer Diameter: 8.0 mm nom.

Weight: 115 kg/km



Design & Materials

Detailed Construction:

The cable conforms to IEC 61156-5 Cat. 7 (tested up to 1000 MHz), Cat. 6_A Cat. 6, and Cat. 5e requirements.

Conductor Material:	Annealed Bare Copper
Conductor Size:	23 AWG
Conductor Size:	0.58 mm
Conductor Construction:	Solid
Insulation Material:	SFS PO
Insulation O.D.:	1.38 mm nom.
Conductor unit identification:	Solid/stripe
Color Code:	Per TIA/EIA 568-B
Ind. Shield Material:	Aluminum/Polyester Foil
Ind. Shield Design:	Aluminum face outwards
Conductor unit lay-up:	Pairs
Drain-wire 1 Material:	Annealed Tinned Copper
Drain-wire 1 Construction:	Solid
Drain-wire 1 size mm.:	0.4 mm
Drain-wire 2 Material:	Annealed Tinned Copper
Drain-wire 2 Construction:	Solid
Drain-wire 2 size:	0.4 (26/1) AWG
Overall Shield Design:	Braid
Overall Shield Material:	Tinned-copper braid
Overall Braid Shield:	Yes
Braid Coverage:	35 % nom.
Total number of conductors:	16
Outer Diameter:	8.2 mm max.
Outer Jacket Dimension - X:	16.7 mm nom.
Outer Jacket Dimension - Y:	8.0 mm nom.
Outer Jacket Color:	Light Gray
Marking:	Per request, Teldor Standard

Standards

Applicable Standards:	IEC 61156, ISO/IEC 11801-1, RoHS 3 2015/863/EU
Flammability Rating:	IEC 60332-1

Electrical Properties:

Cat. 7 Horizontal Cables 1000 MHz*

Freq. MHz	Attenuation dB/100m 20°C		PS NEXT Loss dB		NEXT Loss dB		RL dB		PS ANEXT dB		PS ELFEXT dB		ELFEXT dB	
	Typical Value	Cat. 7	Typical Value	Cat. 7	Typical Value	Cat. 7	Typical Value	Cat. 7	Typical Value	Cat. 7	Typical Value	Cat. 7	Typical Value	Cat. 7
1	2.0	2.0	105.0	99.4	108.0	102.4	22.0	20.0	68.0	N/A	95.0	75.0	98.0	78.0
4	3.6	3.7	98.0	90.4	101.0	93.4	25.0	23.0	68.0	N/A	90.0	75.0	93.0	78.0
10	5.6	5.8	95.0	84.4	98.0	87.4	28.0	25.0	68.0	N/A	86.0	71.0	89.0	74.0
20	7.9	8.3	90.0	80.0	93.0	83.0	28.0	25.0	68.0	N/A	80.0	65.0	83.0	68.0
30	9.7	10.2	85.0	77.2	88.0	80.2	27.0	23.8	68.0	N/A	76.0	61.5	79.0	64.5
100	18.0	19.0	80.0	69.4	83.0	72.4	24.0	21.1	68.0	N/A	66.0	51.0	69.0	54.0
150	22.4	23.6	78.0	66.7	81.0	69.7	22.0	18.8	65.0	N/A	63.0	47.5	66.0	50.5
200	26.0	27.5	78.0	65.0	81.0	68.0	21.0	18.0	65.0	N/A	60.0	45.0	63.0	48.0
250	29.4	31.0	75.0	63.4	78.0	66.4	20.0	17.3	62.0	N/A	58.0	43.0	61.0	46.0
300	32.5	34.2	75.0	62.2	78.0	65.2	19.0	17.3	62.0	N/A	52.0	41.5	55.0	44.5
400	38.0	40.0	70.0	60.4	73.0	63.4	19.0	17.3	62.0	N/A	49.0	38.9	52.0	41.9
500	43.0	45.2	70.0	58.9	73.0	61.9	19.0	17.3	62.0	N/A	47.0	37.0	50.0	40.0
600	47.6	50.1	70.0	57.7	73.0	60.7	19.0	17.3	62.0	N/A	45.0	35.4	48.0	38.4
700	52.0	N/A	70.0	N/A	73.0	63.4	19.0	N/A	60.0	N/A	35.0	N/A	38.0	N/A
900	59.8	N/A	70.0	N/A	73.0	N/A	19.0	N/A	60.0	N/A	32.0	N/A	35.0	N/A
1000	62.0	N/A	70	N/A	73	N/A	19	N/A	58.0	N/A	33.0	N/A	32.0	N/A

*Supplied cables meet the minimum Cat. 7 transmission requirements as per IEC 61156-5 Ed 2

Performance

Frequency Range:	1 - 600 MHz
Impedance:	100 Ω
Coupling Attenuation:	Type I
Max. DC Resistance :	73 Ω/km@20°C
Max. Resistance Unbalance:	2 %
Capacitance Unbalance:	1.3 pF/m max.
Velocity of Propagation:	78 % nom.
Propagation Delay Skew:	20 ns/100m max.
Dielectric Strength:	700 V/minute
Dielectric Strength to Shield:	700 V/minute
Min. Insulation Resistance :	5 GΩ•km
Min. Bend Radius:	80 (small axis) mm
Max. Operating Temperature:	+70 °C
Min. Operating Temperature:	-40 °C

Prepared By	Revised By	Version Num	Modified on
Ofer Solter	Asher Bohbut	1.6	12-03-2013

Teldor Cables & Systems Ltd. ("Teldor") reserves the right to make changes to the products described in this catalog without prior notice. Teldor does not assume any liability which may occur due to the use of the products described herein. Drawings may not be to scale and are provided for general and informational purposes only. The information contained in this catalog is the proprietary property of Teldor, and may not be used, reproduced or disclosed to others, in whole or in part, without the written authorization of Teldor.

Teldor Cables & Systems Ltd. - Ein-Dor, 1933500

ISRAEL

Tel: +972 4 6770555

Fax: +972 4 6770650