

## Cat.7 12x2x22/7 AWG S/FTP Work Area XL-HFFR

**Part Number:** 9928022101

**Applications:** Maritime Environment, Data-Centers/SANs, Indoor Backbone, Work area cabling

**General Construction:** 12 individually foil shielded twisted pairs are concentrically cabled, overall braid shielded and jacketed.

**Detailed Schematic:**

**Outer Jacket Material:** XL-HFFR

**Outer Diameter:** 14 mm nom.

**Weight:** 255 kg/km



### Design & Materials

<b>Conductor Material:</b>	Annealed Tinned Copper
<b>Conductor Size:</b>	22 AWG
<b>Conductor Construction:</b>	7x0.25 mm
<b>Insulation Material:</b>	SFS PO
<b>Insulation O.D.:</b>	1.62 mm nom.
<b>Conductor unit identification:</b>	Numbered
<b>Conductor Color Code:</b>	White x Blue
<b>Ind. Shield Material:</b>	Aluminum/Polyester Foil
<b>Ind. Shield Design:</b>	Helically applied aluminum foil, 100% coverage
<b>Overall Shield Design:</b>	Braid
<b>Overall Braid Shield:</b>	Yes
<b>Overall Braid Material:</b>	Annealed Tinned Copper
<b>Braid Coverage:</b>	70 % nom.
<b>Total number of conductors:</b>	24
<b>Outer Jacket Color:</b>	Black
<b>Marking:</b>	Per request, Teldor Standard

### Standards

<b>Applicable Standards:</b>	, IEC 61156, ISO/IEC 11801-1, RoHS 3 2015/863/EU
<b>Flammability Rating:</b>	IEC 60332-3 , IEC 60754-2, IEC 61034

## Electrical Properties:

Freq. MHz	Attenuation dB/100m 20°C		PS NEXT Loss dB		NEXT Loss dB		RL dB		PS ANEXT dB		PS ELFEXT dB		ELFEXT dB	
	Typical Value	Cat. 7	Typical Value	Cat. 7	Typical Value	Cat. 7	Typical Value	Cat. 7	Typical Value	Cat. 7	Typical Value	Cat. 7	Typical Value	Cat. 7
1	2.0	2.0	105.0	75.0	108.0	78.0	22.0	20.0	68.0	N/A	95.0	75.0	98.0	78.0
4	3.6	3.7	98.0	75.0	101.0	78.0	25.0	23.0	68.0	N/A	90.0	75.0	93.0	78.0
10	5.5	5.8	95.0	75.0	98.0	78.0	28.0	25.0	68.0	N/A	86.0	71.0	89.0	74.0
20	7.7	8.3	90.0	75.0	93.0	78.0	28.0	25.0	68.0	N/A	80.0	65.0	83.0	68.0
30	9.7	10.2	85.0	75.0	88.0	78.0	27.0	23.8	68.0	N/A	76.0	61.5	79.0	64.5
100	17.9	19.0	80.0	69.4	83.0	72.4	24.0	21.1	68.0	N/A	66.0	51.0	69.0	54.0
150	22.4	23.6	78.0	66.7	81.0	69.7	22.0	18.8	65.0	N/A	63.0	47.5	66.0	50.5
200	25.4	27.5	78.0	65.0	81.0	68.0	21.0	18.0	65.0	N/A	60.0	45.0	63.0	48.0
250	28.4	31.0	75.0	63.4	78.0	66.4	20.0	17.3	62.0	N/A	58.0	43.0	61.0	46.0
300	31.5	34.2	75.0	62.2	78.0	65.2	19.0	17.3	62.0	N/A	52.0	41.5	55.0	44.5
400	36.0	40.0	70.0	60.4	73.0	63.4	19.0	17.3	62.0	N/A	49.0	38.9	52.0	41.9
500	41.0	45.2	70.0	58.9	73.0	61.9	19.0	17.3	62.0	N/A	47.0	37.0	50.0	40.0
600	45.6	50.1	70.0	57.7	73.0	60.7	19.0	17.3	62.0	N/A	45.0	35.4	48.0	38.4

\*Supplied cables meet the minimum Cat. 7 transmission requirements as per **IEC 61156-5/6 Ed. 2**

## Performance

<b>Frequency Range:</b>	1 - 600 MHz
<b>Impedance:</b>	100 Ω
<b>Transfer Impedance:</b>	Grade 1
<b>Coupling Attenuation:</b>	Type I
<b>Max. DC Resistance :</b>	65 Ω/km@20°C
<b>Max. Resistance Unbalance:</b>	2 %
<b>Capacitance:</b>	42 pF/m
<b>Capacitance Unbalance:</b>	1.2 pF/m max.
<b>Velocity of Propagation:</b>	78 % nom.
<b>Propagation Delay Skew:</b>	10 ns/100m max.
<b>Dielectric Strength:</b>	500 V/minute
<b>Dielectric Strength to Shield:</b>	300 V/minute
<b>Min. Insulation Resistance :</b>	5 GΩ•km
<b>Min. Bend Radius:</b>	110 mm
<b>Max. Operating Temperature:</b>	+70 °C
<b>Min. Operating Temperature:</b>	-30 °C
<b>UV Resistance:</b>	Yes

Prepared By	Revised By	Version Num	Modified on
Ofer Solter	Eyal Stroumza	1.11	13-02-2017

Teldor Cables & Systems Ltd. ("Teldor") reserves the right to make changes to the products described in this catalog without prior notice. Teldor does not assume any liability which may occur due to the use of the products described herein. Drawings may not be to scale and are provided for general and informational purposes only. The information contained in this catalog is the proprietary property of Teldor, and may not be used, reproduced or disclosed to others, in whole or in part, without the written authorization of Teldor.

**Teldor Cables & Systems Ltd.** - Ein-Dor, 1933500

ISRAEL

Tel: +972 4 6770555

Fax: +972 4 6770650