

Composite Cable [10x(Work area cable) + 2x(RG-59)]

Part Number: **4T00090101**

Applications:

Indoor/Outdoor use, fixed installations

General Construction:

Contains 10 work area data cables (P/N 9928244XXX), and 2 coax cables - RG-59 (P/N 6305920XXX). Each internal work area cable contains 4 individually foil-shielded twisted pairs, cabled, overall braid-shielded, jakceted with FR-LSZH compound, and is compatible with RJ-45 modular plugs.
The 10 work area cables, and the 2 coax cables are cabled together with filler elements, separation tape, and jacketed with PU compound.
The coax cable transmission properties comply whit RG-59 standart.



Outer Jacket Material:

PU

Outer Diameter:

27.5 mm nom.

Weight:

678 kg/km

Design & Materials

Conductor Material:	Annealed Bare Copper
Conductor Size:	26 AWG
Conductor Construction:	7x0.17 mm
Insulation Material:	SFS PO
Insulation O.D.:	1.0 mm nom.
Conductor unit identification:	Solid/stripe
Color Code:	Per TIA/EIA 568-B
Ind. Shield Material:	Aluminum/Polyester Foil
Ind. Shield Design:	Aluminum face outwards
Conductor unit lay-up:	Pairs
Overall Braid Shield:	Yes
Braid Coverage:	51 % nom.
Inner Jacket Material:	FR-LSZH
Inner Jacket Thickness:	0.45 mm nom.
Inner Jacket Diameter nom.:	6.1 mm nom
Inner Jacket Color:	Light Gray - or per request
Outer Jacket Color:	Black
Marking:	Per request, Teldor Standard

Standards

Applicable Standards:	IEC 61156, ISO/IEC 11801-1
Flammability Rating:	IEC 60332-1

Electrical Properties:

Cat. 7 Work Area Cables*

Freq. MHz	Attenuation dB/100m 20°C		PS NEXT Loss dB		NEXT Loss dB		RL dB		PS ANEXT dB		PS ELFEXT dB		ELFEXT dB	
	Typical Value	Cat. 7	Typical Value	Cat. 7	Typical Value	Cat. 7	Typical Value	Cat. 7	Typical Value	Cat. 7	Typical Value	Cat. 7	Typical Value	Cat. 7
1	2.9	3.0	105.0	99.4	108.0	102.4	22.0	20.0	68.0	N/A	95.0	75.0	98.0	78.0
4	5.4	5.6	98.0	90.4	101.0	93.4	25.0	23.0	68.0	N/A	90.0	75.0	93.0	78.0
10	8.5	8.8	95.0	84.4	98.0	87.4	28.0	25.0	68.0	N/A	86.0	71.0	89.0	74.0
20	12.1	12.4	90.0	80.0	93.0	83.0	28.0	25.0	68.0	N/A	80.0	65.0	83.0	68.0
30	14.8	15.3	85.0	77.2	88.0	80.2	27.0	23.8	68.0	N/A	76.0	61.5	79.0	64.5
100	27.7	28.5	80.0	69.4	83.0	72.4	24.0	21.1	68.0	N/A	66.0	51.0	69.0	54.0
150	34.3	35.3	78.0	66.7	81.0	69.7	22.0	18.8	65.0	N/A	63.0	47.5	66.0	50.5
200	40.0	41.2	78.0	65.0	81.0	68.0	21.0	18.0	65.0	N/A	60.0	45.0	63.0	48.0
250	45.1	46.5	75.0	63.4	78.0	66.4	20.0	17.3	62.0	N/A	58.0	43.0	61.0	46.0
300	49.7	51.3	75.0	62.2	78.0	65.2	19.0	17.3	62.0	N/A	52.0	41.5	55.0	44.5
400	58.2	60.0	70.0	60.4	73.0	63.4	19.0	17.3	62.0	N/A	49.0	38.9	52.0	41.9
500	65.8	67.9	70.0	58.9	73.0	61.9	19.0	17.3	62.0	N/A	47.0	37.0	50.0	40.0
600	72.9	75.1	70.0	57.7	73.0	60.7	19.0	17.3	62.0	N/A	45.0	35.4	48.0	38.4

*Supplied cables meet the minimum Cat. 7 transmission requirements as per **IEC 61156-6 Ed. 2**

Performance

Frequency Range:	1 - 600 MHz
Coupling Attenuation:	Type I
DC Resistance:	145 Ω/km nom.
Max. Resistance Unbalance:	2 %
Capacitance Unbalance:	1.2 pF/m max.
Velocity of Propagation:	80 % nom.
Propagation Delay Skew:	20 ns/100m max.
Dielectric Strength:	700 V/minute
Min. Insulation Resistance :	5 GΩ•km
Max. Operating Temperature:	60 °C
Min. Operating Temperature:	-40 °C

Prepared By	Revised By	Version Num	Modified on
		1.17	01-07-2008

Teldor Cables & Systems Ltd. ("Teldor") reserves the right to make changes to the products described in this catalog without prior notice. Teldor does not assume any liability which may occur due to the use of the products described herein. Drawings may not be to scale and are provided for general and informational purposes only. The information contained in this catalog is the proprietary property of Teldor, and may not be used, reproduced or disclosed to others, in whole or in part, without the written authorization of Teldor.

Teldor Cables & Systems Ltd. - Ein-Dor, 1933500

ISRAEL

Tel: +972 4 6770555

Fax: +972 4 6770650