


Cat. 7 4x2x23/1 AWG S/FTP FR-LSZH

Part Number: 9928001129

- Applications:** Optimized for IEEE 802.3bt 4PPoE, Data processing and information systems, Fixed or portable installations, High data rates, Indoor use, fixed installations
- General Construction:** 4 individually foil-shielded twisted pairs, cabled together with tinned copper drain conductor, overall braid-shielded and jacketed.
The cable conforms to IEC 61156-5 Cat. 7, Cat. 6_A Cat. 6, and Cat. 5e requirements and tested up to 1000 MHz.
- Outer Jacket Material:** FR-LSZH
- Outer Diameter:** 7.1 mm nom.
- Weight:** 50 kg/km



Design & Materials

Conductor Material:	Annealed Bare Copper
Conductor Size:	23 AWG
Conductor Construction:	Solid
Insulation Material:	Cellular PO
Insulation O.D.:	1.38 mm nom.
Conductor unit identification:	Solid/stripe
Color Code:	Per TIA/EIA 568-B
Ind. Shield Material:	Aluminum/Polyester Foil
Ind. Shield Design:	100% Coverage
Conductor unit lay-up:	Pairs
Overall Braid Shield:	Yes
Braid Coverage:	35 % nom.
Overall Drain-wire Material:	Annealed Tinned Copper
Overall Drain-wire size:	0.41 mm
Overall Drain-wire Construction:	Solid
Total number of conductors:	8
Outer Jacket Color:	Light Gray
Marking:	Per request, Teldor Standard

Standards

Applicable Standards:	IEC 61156-5, IEC 61156, IEEE 802.3at (PoE+), IEEE 802.3af (PoE), IEEE 802.3bt (4PPoE), ISO/IEC 11801-1, RoHS 3 2015/863/EU
Flammability Rating:	IEC 60332-1, UL 1581 VW-1, EN 50575:2014 Dcas2d2a2 (CPR)

Electrical Properties:

Cat. 7 Horizontal Cables*

Freq. MHz	Attenuation dB/100m 20°C		PS NEXT Loss dB		NEXT Loss dB		RL dB		PS ANEXT dB		PS ELFEXT dB		ELFEXT dB	
	Typical Value	Cat. 7	Typical Value	Cat. 7	Typical Value	Cat. 7	Typical Value	Cat. 7	Typical Value	Cat. 7	Typical Value	Cat. 7	Typical Value	Cat. 7
1	2.0	2.0	105.0	75.0	108.0	78.0	22.0	20.0	68.0	N/A	95.0	75.0	98.0	78.0
4	3.6	3.7	98.0	75.0	101.0	78.0	25.0	23.0	68.0	N/A	90.0	75.0	93.0	78.0
10	5.6	5.8	95.0	75.0	98.0	78.0	28.0	25.0	68.0	N/A	86.0	71.0	89.0	74.0
20	7.9	8.3	90.0	75.0	93.0	78.0	28.0	25.0	68.0	N/A	80.0	65.0	83.0	68.0
30	9.7	10.2	85.0	75.0	88.0	78.0	27.0	23.8	68.0	N/A	76.0	61.5	79.0	64.5
100	18.0	19.0	80.0	69.4	83.0	72.4	24.0	21.1	68.0	N/A	66.0	51.0	69.0	54.0
150	22.4	23.6	78.0	66.7	81.0	69.7	22.0	18.8	65.0	N/A	63.0	47.5	66.0	50.5
200	26.0	27.5	78.0	65.0	81.0	68.0	21.0	18.0	65.0	N/A	60.0	45.0	63.0	48.0
250	29.4	31.0	75.0	63.4	78.0	66.4	20.0	17.3	62.0	N/A	58.0	43.0	61.0	46.0
300	32.5	34.2	75.0	62.2	78.0	65.2	19.0	17.3	62.0	N/A	52.0	41.5	55.0	44.5
400	38.0	40.0	70.0	60.4	73.0	63.4	19.0	17.3	62.0	N/A	49.0	38.9	52.0	41.9
500	43.0	45.2	70.0	58.9	73.0	61.9	19.0	17.3	62.0	N/A	47.0	37.0	50.0	40.0
600	47.6	50.1	70.0	57.7	73.0	60.7	19.0	17.3	62.0	N/A	45.0	35.4	48.0	38.4

*Supplied cables meet the minimum Cat. 7 transmission requirements as per IEC 61156-5 Ed. 2

Performance

Frequency Range:	1 - 1000 MHz
Impedance:	100 Ω
Coupling Attenuation:	Type I
Max. DC Resistance :	73 Ω/km@20°C
Max. Resistance Unbalance:	2 %
Capacitance Unbalance:	1.2 pF/m max.
Velocity of Propagation:	78 % nom.
Propagation Delay Skew:	25 ns/100m max.
Dielectric Strength:	700 V/minute
Dielectric Strength to Shield:	700 V/minute
Min. Insulation Resistance :	5 GΩ•km
Min. Bend Radius:	60 mm
Max. Operating Temperature:	+65 °C
Min. Operating Temperature:	-40 °C

Prepared By	Revised By	Version Num	Modified on
Asher Bohbut	Eyal Stroumza	3.9	03-01-2024

Teldor Cables & Systems Ltd. ("Teldor") reserves the right to make changes to the products described in this catalog without prior notice. Teldor does not assume any liability which may occur due to the use of the products described herein. Drawings may not be to scale and are provided for general and informational purposes only. The information contained in this catalog is the proprietary property of Teldor, and may not be used, reproduced or disclosed to others, in whole or in part, without the written authorization of Teldor.

Teldor Cables & Systems Ltd. - Ein-Dor, 1933500
6770650

ISRAEL

Tel: +972 4 6770555

Fax: +972 4