

Cat.7 12x2x26/1 AWG S/FTP Work Area FR-LSZH

Part Number: 9928009129

Applications: Data-Centers/SANs, Work area cabling, Indoor Backbone, Indoor use, fixed or portable installations


General Construction: 12 foil-shielded twisted pairs grouped into 3 groups. each group identified with numbered tape. The 3 groups are cabled together, overall tinned copper braid shielded and jacketed with FR-LSZH compound for indoor use. The insulated conductors are compatible for use with screened RJ-45 modular plugs.

Detailed Schematic:

Outer Jacket Material: FR-LSZH

Outer Diameter: 12.6 mm nom.

Weight: 154 kg/km



Design & Materials

Detailed Construction:

The electrical and transmission properties are referred to each 4 pair marked group

Conductor Material:	Annealed Bare Copper
Conductor Size:	0.42 mm
Conductor Construction:	Solid
Insulation Material:	SFS PO
Insulation O.D.:	1.0 mm nom.
Conductor unit identification:	Solid/stripe
Color Code:	Per TIA/EIA 568-B
Ind. Shield Material:	Aluminum/Polyester Foil
Ind. Shield Design:	100% Coverage
Overall Braid Shield:	Yes
Braid Coverage:	85 % nom.
Total number of conductors:	24
Outer Jacket Color:	Light Gray
Marking:	Per request, Teldor Standard

Standards

Applicable Standards:	IEC 61156, ISO/IEC 11801-1, RoHS 3 2015/863/EU
Flammability Rating:	IEC 60332-3 , UL 1581 VW-1

Electrical Properties:

Cat. 7 Work Area Cables*

Freq. MHz	Attenuation dB/100m 20°C		PS NEXT Loss dB		NEXT Loss dB		RL dB		PS ANEXT dB		PS ELFEXT dB		ELFEXT dB	
	Typical Value	Cat. 7	Typical Value	Cat. 7	Typical Value	Cat. 7	Typical Value	Cat. 7	Typical Value	Cat. 7	Typical Value	Cat. 7	Typical Value	Cat. 7
1	2.9	3.0	105.0	99.4	108.0	102.4	22.0	20.0	68.0	N/A	95.0	75.0	98.0	78.0
4	5.4	5.6	98.0	90.4	101.0	93.4	25.0	23.0	68.0	N/A	90.0	75.0	93.0	78.0
10	8.5	8.8	95.0	84.4	98.0	87.4	28.0	25.0	68.0	N/A	86.0	71.0	89.0	74.0
20	12.1	12.4	90.0	80.0	93.0	83.0	28.0	25.0	68.0	N/A	80.0	65.0	83.0	68.0
30	14.8	15.3	85.0	77.2	88.0	80.2	27.0	23.8	68.0	N/A	76.0	61.5	79.0	64.5
100	27.7	28.5	80.0	69.4	83.0	72.4	24.0	21.1	68.0	N/A	66.0	51.0	69.0	54.0
150	34.3	35.3	78.0	66.7	81.0	69.7	22.0	18.8	65.0	N/A	63.0	47.5	66.0	50.5
200	40.0	41.2	78.0	65.0	81.0	68.0	21.0	18.0	65.0	N/A	60.0	45.0	63.0	48.0
250	45.1	46.5	75.0	63.4	78.0	66.4	20.0	17.3	62.0	N/A	58.0	43.0	61.0	46.0
300	49.7	51.3	75.0	62.2	78.0	65.2	19.0	17.3	62.0	N/A	52.0	41.5	55.0	44.5
400	58.2	60.0	70.0	60.4	73.0	63.4	19.0	17.3	62.0	N/A	49.0	38.9	52.0	41.9
500	65.8	67.9	70.0	58.9	73.0	61.9	19.0	17.3	62.0	N/A	47.0	37.0	50.0	40.0
600	72.9	75.1	70.0	57.7	73.0	60.7	19.0	17.3	62.0	N/A	45.0	35.4	48.0	38.4

*Supplied cables meet the minimum Cat. 7 transmission requirements as per **IEC 61156-6 Ed. 2**

Performance

Frequency Range:	1 - 600 MHz
Coupling Attenuation:	Type I
Max. DC Resistance :	140 Ω/km@20°C
Max. Resistance Unbalance:	2 %
Max. Screen Resistance:	30 Ω/Km @20°C
Capacitance Unbalance:	1.2 pF/m max.
Velocity of Propagation:	78 % nom.
Propagation Delay Skew:	35 ns/100m max.
Dielectric Strength:	500 V/minute
Dielectric Strength to Shield:	300 V/minute
Min. Insulation Resistance :	5 GΩ•km
Min. Bend Radius:	130 mm
Max. Operating Temperature:	+60 °C
Min. Operating Temperature:	-35 °C

Prepared By	Revised By	Version Num	Modified on
Jacob Ben Ary	Jacob Ben Ary	2.3	30-07-2013

Teldor Cables & Systems Ltd. ("Teldor") reserves the right to make changes to the products described in this catalog without prior notice. Teldor does not assume any liability which may occur due to the use of the products described herein. Drawings may not be to scale and are provided for general and informational purposes only. The information contained in this catalog is the proprietary property of Teldor, and may not be used, reproduced or disclosed to others, in whole or in part, without the written authorization of Teldor.

Teldor Cables & Systems Ltd. - Ein-Dor, 1933500
6770650

ISRAEL

Tel: +972 4 6770555

Fax: +972 4