

Cat. 7 2x(4x2x23/1 AWG) F/FTP Grade-3 FR-LSZH

Part Number: 9827C58129


Applications: High data rates, High bandwidth digital applications with low BER, Indoor use, fixed installations

General Construction: The cable contains 8 individually foil-shielded twisted pairs, cabled together with a drain wire into 2 cores, each core overall shielded with an aluminum foil, jacketed with a FR-LSZH compound in a fig. 8 configuration. This cable conforms to the IEC 61156-5 Cat. 7, Cat 6_A, Cat. 6 and Cat. 5e requirements and **tested up to 900 MHz**.

Detailed Schematic:

Outer Jacket Material: FR-LSZH

Weight: 110 kg/km



Design & Materials

Conductor Material:	Annealed Bare Copper
Conductor Size:	23 AWG
Conductor Construction:	Solid
Insulation Material:	SFS PO
Insulation O.D.:	1.35 mm nom.
Color Code:	Per TIA/EIA 568-B
Ind. Shield Material:	Aluminum/Polyester Foil
Ind. Shield Design:	Helically applied aluminum foil, 100% coverage
Overall Shield Design:	Helically applied aluminum foil, 100% coverage
Overall Shield Material:	Aluminum/Polyester Foil
Overall Foil Shield:	Yes
Overall Drain-wire Material:	Annealed Tinned Copper
Overall Drain-wire size:	0.41 mm
Overall Drain-wire Construction:	Solid
Total number of conductors:	16
Outer Jacket Dimension - X:	15.5 mm nom.
Outer Jacket Dimension - Y:	7.5 mm nom.
Outer Jacket Color:	Light Gray
Marking:	Per request, Teldor Standard

Standards

Applicable Standards:	IEC 61156, ISO/IEC 11801-1, RoHS 3 2015/863/EU
Flammability Rating:	IEC 60332-1

Electrical Properties:

Cat. 7 Horizontal Cables*

Freq. MHz	Attenuation dB/100m 20°C		PS NEXT Loss dB		NEXT Loss dB		RL dB		PS ANEXT dB		PS ELFEXT dB		ELFEXT dB	
	Typical Value	Cat. 7	Typical Value	Cat. 7	Typical Value	Cat. 7	Typical Value	Cat. 7	Typical Value	Cat. 7	Typical Value	Cat. 7	Typical Value	Cat. 7
1	2.0	2.0	105.0	75.0	108.0	78.0	22.0	20.0	68.0	N/A	95.0	75.0	98.0	78.0
4	3.6	3.7	98.0	75.0	101.0	78.0	25.0	23.0	68.0	N/A	90.0	75.0	93.0	78.0
10	5.6	5.8	95.0	75.0	98.0	78.0	28.0	25.0	68.0	N/A	86.0	71.0	89.0	74.0
20	7.9	8.3	90.0	75.0	93.0	78.0	28.0	25.0	68.0	N/A	80.0	65.0	83.0	68.0
30	9.7	10.2	85.0	75.0	88.0	78.0	27.0	23.8	68.0	N/A	76.0	61.5	79.0	64.5
100	18.0	19.0	80.0	69.4	83.0	72.4	24.0	21.1	68.0	N/A	66.0	51.0	69.0	54.0
150	22.4	23.6	78.0	66.7	81.0	69.7	22.0	18.8	65.0	N/A	63.0	47.5	66.0	50.5
200	26.0	27.5	78.0	65.0	81.0	68.0	21.0	18.0	65.0	N/A	60.0	45.0	63.0	48.0
250	29.4	31.0	75.0	63.4	78.0	66.4	20.0	17.3	62.0	N/A	58.0	43.0	61.0	46.0
300	32.5	34.2	75.0	62.2	78.0	65.2	19.0	17.3	62.0	N/A	52.0	41.5	55.0	44.5
400	38.0	40.0	70.0	60.4	73.0	63.4	19.0	17.3	62.0	N/A	49.0	38.9	52.0	41.9
500	43.0	45.2	70.0	58.9	73.0	61.9	19.0	17.3	62.0	N/A	47.0	37.0	50.0	40.0
600	47.6	50.1	70.0	57.7	73.0	60.7	19.0	17.3	62.0	N/A	45.0	35.4	48.0	38.4

*Supplied cables meet the minimum Cat. 7 transmission requirements as per **IEC 61156-5 Ed. 2**

Performance

Frequency Range:	1 - 900 MHz
Impedance:	100 Ω
Coupling Attenuation:	Type II
Max. Resistance Unbalance:	2 %
Capacitance Unbalance:	1.2 pF/m max.
Velocity of Propagation:	78 % nom.
Propagation Delay Skew:	20 ns/100m max.
Dielectric Strength:	700 V/minute
Dielectric Strength to Shield:	700 V/minute
Min. Insulation Resistance :	5 GΩ•km
Min. Bend Radius:	80 (small axis) mm
Max. Operating Temperature:	+60 °C
Min. Operating Temperature:	-40 °C

Prepared By	Revised By	Version Num	Modified on
Ofer Solter	Jacob Ben Ary	1.10	03-05-2012

Teldor Cables & Systems Ltd. ("Teldor") reserves the right to make changes to the products described in this catalog without prior notice. Teldor does not assume any liability which may occur due to the use of the products described herein. Drawings may not be to scale and are provided for general and informational purposes only. The information contained in this catalog is the proprietary property of Teldor, and may not be used, reproduced or disclosed to others, in whole or in part, without the written authorization of Teldor.

Teldor Cables & Systems Ltd. - Ein-Dor, 1933500

ISRAEL

Tel: +972 4 6770555

Fax: +972 4 6770650